

LED lighting products designed and manufactured in England by Light Visuals.

DATA SHEET

The LV-806 is a surface mounted LED light suitable for installing into borders with low level plants. The addition of the 300mm extension pole raises the fixture above the small plants below allowing the product to be hidden, whilst not restricting the light output. The LV-806 is for mounting into soil via the 3x 316L stainless steel mounting spikes. Choose product LV-805 for secure fixing with the use of 3x screws through the floor mounting plate. Available in black anodised aluminium, or 316L stainless steel. Light Visuals products are made to order. (Please allow 3 weeks for delivery). Designed, manufactured, and hand assembled in England Black anodised aluminium 6082 construction Wiring to be in (SERIES) Requires a remote (constant current) LED driver 700mA maximum 77mm • 350mA = 1.2w, 500mA = 1.7w, 700mA = 2.4w drivers can be used Forward voltage: 3.2v DC 300mm Colour temperature: 2700K (warm white) • Light source: Cree XP-E (integral LED) • BIN: 8B4 CRI 85 79.98lm@350mA 139.96lm@700mA (Typical) • Dimmable 0-10V Beam choice; 10°, 18°, 32°, 42° • IP68 1m 2 core HO5RN-F rubber cable 5 year guarantee Product code: LV-BL806 150mm

LV-BL806 Triple spike extension pole light

Light Visuals products have been independently tested and certified by a UKAS registered laboratory in the UK.

April 2015