



Exterior Lights UK Ltd

The Orpington is a modern and stylish IP55 rated stainless steel LED Bollard.

Manufactured from 316 Stainless Steel, featuring aluminium louvres for optimum performance and a transparent strong UV stabilised polycarbonate diffuser.

Options available include bolt-on root, 180° spill shield and 3hr emergency.



Orpington 30W - LED Bollard

Bollard Lighting



Features


- LED rating 3,920lm (4000K & 6000K).
- LED rating 3,316lm (3000K).
- Luminaire flux 2,783lm (4000K & 6000K).
- Luminaire flux 2,355lm (3000K).
- 3000K (WW), 4000K (NW) and 6000K (CW) colour temperature options.
- -20 to +40°C operating temperature (Emergency 0 to +40°C).
- LED life span > 100,000hrs.
- Osram LED and Osram Driver.
- Easy access to LED and Driver via a removable head.
- Aluminium louvres for optimum performance and minimal upward light.
- Tamper proof fixings for increased vandal resistance.
- Marine Grade 316.

Applications

- Prestigious Grounds
- Walk Ways
- Car Parks
- Security
- Parks and Gardens
- Amenity Areas

www.exteriorlights.co.uk

01689 606 342



Specifications

Orpington 30W

Item Number	Description	Light Source	LED Rating (lm)	Total Wattage (W)	Colour Name	CCT (K)	CRI	Voltage (VAC)	Driver Current (mA)	Luminaire Flux (lm)	Luminaire Efficacy (lm/W)	Kg	Unit Colour
Standard													
AB30-A5C-00-SS316	Orpington-30W-LED-AC-6K-Std-SS316	LED	3,920	30	CW	6K	Ra>70	220-240	525	2,783	93	8.5	SS316
AB30-A5N-00-SS316	Orpington-30W-LED-AC-4K-Std-SS316	LED	3,920	30	NW	4K	Ra>70	220-240	525	2,783	93	8.5	SS316
AB30-A5W-00-SS316	Orpington-30W-LED-AC-3K-Std-SS316	LED	3,316	30	WW	3K	Ra>80	220-240	525	2,355	78	8.5	SS316
Standard - Emergency													
AB30-A5C-01-SS316	Orpington-30W-LED-AC-6K-Std-E3-SS316	LED	3,920	30	CW	6K	Ra>70	220-240	525	2,783	93	9.5	SS316
AB30-A5N-01-SS316	Orpington-30W-LED-AC-4K-Std-E3-SS316	LED	3,920	30	NW	4K	Ra>70	220-240	525	2,783	93	9.5	SS316
AB30-A5W-01-SS316	Orpington-30W-LED-AC-3K-Std-E3-SS316	LED	3,316	30	WW	3K	Ra>80	220-240	525	2,355	78	9.5	SS316
Dali													
AB30-A5C-20-SS316	Orpington-30W-LED-AC-6K-Dali-SS316	LED	3,920	30	CW	6K	Ra>70	220-240	525	2,783	93	8.5	SS316
AB30-A5N-20-SS316	Orpington-30W-LED-AC-4K-Dali-SS316	LED	3,920	30	NW	4K	Ra>70	220-240	525	2,783	93	8.5	SS316
AB30-A5W-20-SS316	Orpington-30W-LED-AC-3K-Dali-SS316	LED	3,316	30	WW	3K	Ra>80	220-240	525	2,355	78	8.5	SS316
Dali - Emergency													
AB30-A5C-21-SS316	Orpington-30W-LED-AC-6K-Dali-E3-SS316	LED	3,920	30	CW	6K	Ra>70	220-240	525	2,783	93	9.5	SS316
AB30-A5N-21-SS316	Orpington-30W-LED-AC-4K-Dali-E3-SS316	LED	3,920	30	NW	4K	Ra>70	220-240	525	2,783	93	9.5	SS316
AB30-A5W-21-SS316	Orpington-30W-LED-AC-3K-Dali-E3-SS316	LED	3,316	30	WW	3K	Ra>80	220-240	525	2,355	78	9.5	SS316

Legend: **Std** = Standard. **M/Photocell** = Mini Photocell. **3K** = Warm White (3000K). **4K** = Neutral White (4000K). **6K** = Cool White (6000K). **WW** = Warm White. **NW** = Neutral White. **CW** = Cool White.