



## Exterior Lights UK Ltd

The Whitstable 100W is an IP65/IK08 robust and durable LED Flood Light.

Manufactured with a die-cast aluminium body, 4mm thick toughened glass panel and pre-wired with 700mm of cable.

Available In CCT 3000K or 4000K and with a choice of 3 optics types offering Symmetrical and Asymmetrical light distributions.

Nema socket option available for dusk to dawn switching.



# Whitstable 100W - LED Flood Light

## Flood Lighting



## Features

- LED rating 12,750lm (4000K).
- LED rating 10,774lm (3000K).
- Luminaire flux 12,113lm (4000K).
- Luminaire flux 10,235lm (3000K).
- 3000K (WW) and 4000K (NW) colour temperature options.
- IP65/IK08 rated.
- -20 to +40 operating temperature.
- LED life span > 65,000hrs.
- Universal bracket for T/Bar bracket and wall fixing.
- 4mm thick toughened glass panel.
- Pre-wired with 700mm of cable.
- 3 optics types offering Symmetrical and Asymmetrical light distributions.

## Applications

- Security
- Sport
- Car Parks
- Perimeter Fence
- Canopy
- Facade

[www.exteriorlights.co.uk](http://www.exteriorlights.co.uk)

01689 606 342