



Specifications

Whitstable 100W

Item Number	Description	Light Source	LED Rating (lm)	Total Wattage (W)	Colour Name	CCT (K)	CRI	Voltage (VAC)	Luminaire Flux (lm)	Luminaire Efficacy (lm/W)	Kg	Unit Colour
Standard (4000K)												
DR100-AN-00B-1	Whitstable-100W-LED-AC-4K-Std-Black-Optic1	LED	12,750	100	NW	4K	Ra>70	220-240	12,113	121	4.0	Black
DR100-AN-00B-2	Whitstable-100W-LED-AC-4K-Std-Black-Optic 2	LED	12,750	100	NW	4K	Ra>70	220-240	12,113	121	4.0	Black
DR100-AN-00B-3	Whitstable-100W-LED-AC-4K-Std-Black-Optic 3	LED	12,750	100	NW	4K	Ra>70	220-240	12,113	121	4.0	Black
Standard (3000K)												
DR100-AW-00B-1	Whitstable-100W-LED-AC-3K-Std-Black-Optic1	LED	10,774	100	WW	3K	Ra>80	220-240	10,235	102	4.0	Black
DR100-AW-00B-2	Whitstable-100W-LED-AC-3K-Std-Black-Optic 2	LED	10,774	100	WW	3K	Ra>80	220-240	10,235	102	4.0	Black
DR100-AW-00B-3	Whitstable-100W-LED-AC-3K-Std-Black-Optic 3	LED	10,774	100	WW	3K	Ra>80	220-240	10,235	102	4.0	Black
Standard-NemaSocket (4000K)												
DR100-AN-05B-1	Whitstable-100W-LED-AC-4K-Std-Nema Socket-Black-Optic1	LED	12,750	100	NW	4K	Ra>70	220-240	12,113	121	4.0	Black
DR100-AN-05B-2	Whitstable-100W-LED-AC-4K-Std-Nema Socket-Black-Optic 2	LED	12,750	100	NW	4K	Ra>70	220-240	12,113	121	4.0	Black
DR100-AN-05B-3	Whitstable-100W-LED-AC-4K-Std-Nema Socket-Black-Optic 3	LED	12,750	100	NW	4K	Ra>70	220-240	12,113	121	4.0	Black
Standard-NemaSocket (3000K)												
DR100-AW-05B-1	Whitstable-100W-LED-AC-3K-Std-Nema Socket-Black-Optic1	LED	10,774	100	WW	3K	Ra>80	220-240	10,235	102	4.0	Black
DR100-AW-05B-2	Whitstable-100W-LED-AC-3K-Std-Nema Socket-Black-Optic 2	LED	10,774	100	WW	3K	Ra>80	220-240	10,235	102	4.0	Black
DR100-AW-05B-3	Whitstable-100W-LED-AC-3K-Std-Nema Socket-Black-Optic 3	LED	10,774	100	WW	3K	Ra>80	220-240	10,235	102	4.0	Black