

DOLIX OUT QPAR51

round, white

The DOLIX OUT high-voltage recessed ceiling ring is made from aluminium and is equipped with a glass for protection against splashing water. Rated IP65 it can be used outdoors or in damp areas. Thanks to the already incorporated GU10 high-voltage socket, the DOLIX OUT recessed ceiling ring is ready for direct connection to 230V mains supply.

TECHNICAL DATA

| Item no.: | 1001165 | | |
|-------------------------|---------------------------|--|--|
| Socket | GU10 | | |
| Lamp | QPAR51 | | |
| Number of sockets | 1 | | |
| Lamps included | 0 | | |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V | | |
| Height | 11.0 cm | | |
| Diameter | 8.2 cm | | |
| Installation diameter | 6.8 cm | | |
| Installation depth | 11.0 cm | | |
| Net weight | 0.192 kg | | |
| Gross weight | 0.229 kg | | |
| IP Code | IP 65 | | |
| Safety class | II | | |
| Impact resistance class | IK02 | | |
| Impact resistance | 0,20000000000000001 Joule | | |
| Assembly | Recessed | | |
| Assembly details | Ceiling | | |
| Wattage | 50.0 W | | |
| Color | white | | |
| BIG WHITE Page | 461 | | |
| | | | |





Recommended lamp

| 1001918 | VALETO® LED lamp , GU10, 2700-6500K, 48°, 5.1W |
|---------|---|
| 1001919 | VALETO® LED lamp , GU10, RGBW, 60°, 5.6W |

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |