

GU10 BULB 400LM 3.6W 2700K NON-DIMM 36 BEAM INTEGRAL

ILGU10NC102



The Integral LED Classic GU10 range offers a fantastic ratio of value and performance. By incorporating a stylish engineered lens in an affordable GU10, the Classic offers directional light with a beam angle that closely mirrors that of familiar halogen lamps along with all the energy-saving and long-life benefits of LED.

Details

Quick Order Code: 353257

Barcode: 5055788240976

Category:LampsRange Name:ClassicProduct Type:GU10Product Body Finish:Matt white

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2
CE RoHS: Yes

Physical Data

Product Length (mm): 54
Product Width (mm): 50
Product Weight (g): 23

Optic: Designed to give a Classic Look

Material: Plastic and Aluminium heat-sink, Injection moulded

diffuser

Base Term: GU10
Bulb Base: GU10

Construction: Plastic White and "Classic look" difuser lens

Globe Finish: Clear
Bulb Fixing: Downlight
Bulb or Luminaire Shape: Round

Placement / Application: Indoor, General Lighting
Spot Type: SMD with "COB like effect"

Electrical Data

Power (W): 3.6 Power Consumption (W): 3.6 Power Factor: 0.4
Wattage equivalent (W): 50
Amperage (mA): 28

Dimming: Non-Dimmable

Driver Included:YesElectric Current:ACTrue Wattage Eq (W):50

EN: EN-62560

LVD Certified: Yes

Light Data

Luminous Flux in Lumens (Im): 400
Luminous efficacy (Im/W): 96
Peak Intensity (Cd): 700
Correlated Colour Temperature (CCT) (K): 2700

Colour Temperature: 2700K - Warm

Colour Temperature Name:WarmBeam Angle:36Colour Rendering Index (CRI):80Frequency Range (Hz):50/60Instant on (Less than 1 second):Yes


LED Type: Surface mounted device (SMD)


Lifetime (hours): 15000
Switching Cycles: 7500
Useful Lumens (lm): 345

Environment

EN: EN-62560

LVD Certified: Yes **CE RoHS:** Yes **Previous Energy Rating:** A++ E **New Energy Rating:** Hg 0% (Mercury Free): Yes **IP Rating (Ingress Protection):** IP20 **Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 40





Packaging

Package Weight (g):35Package Length (mm):60Package Width (mm):55Package Depth (mm):55Qty per euro pallet:3000