

# **Product Specification Sheet**

## MR16 Glass GU5.3 4.8W (37W) 4000K 470lm Non-Dimmable Lamp

Partcode: ILMR16NE030 / Page: 1



The glass body and cleverly engineered surface mounted LEDs of the Integral LED Glass MR16 range give them an attractive look that is very similar to traditional halogen lamps.

These MR16 lamps will retrofit easily into existing fittings and provide significant energy savings and longer lifetime than the halogen lamps they are designed to replace.

#### **Product Details**

Range Name: Glass

Partcode: ILMR16NE030 Check Code: 282697

Placement / Application: Indoor, General Lighting

Market Segment: Commercial indoor, Residential indoor

Product Type: MR16 Warranty: 2 Years CE / RoHS: Yes

#### **Physical Data**

Base Type: GU5.3

Spot Type: SMD with "COB like effect"

Optic: Designed to give a Halogen look

Material: Aluminium, Glass

Construction: Glass with Aluminium heat-sink, Injection moulded diffuser



# **Product Specification Sheet**

Partcode: ILMR16NE030 / Page: 2

### **Physical Data**

Length: 44mm Width: 50mm

Weight (Unpackaged Single Unit): 43g

Lamp or Luminaire Shape: Round

Lamp Fixing: Downlight

#### **Electrical Data**

Voltage Range: 12V

Power Consumption: 4.8 Watts

Driver included: No, needs 12V AC Transformer

Driver IC Manufacturer: IWATT

Electric Current: AC Ampage: 580.00mA

Frequency Range: 50 Hz Power Factor: >=0.60

Wattage Equivalent: 38 Watts

Dimming: Non-dimmable

LVD Certified: Yes EN: EN-62560

### **Light Data**

Useful Lumens: 400lm (Rated luminous flux in a 90° cone)

Lumens: 470lm

Lumens per Watt: 98.0lm/W

Peak Intensity: 650Cd

Beam Angle: 36°

Correlated Colour Temperature (CCT): 4000k

Colour Temperature: Cool White Colour Rendering Index (CRI): >=80

LED Type: Surface mounted device (SMD)

LED Size: 2835

Instant on - Less than 1 second: Yes

Lifetime: 15,000 hrs


Switching Cycles: >7,500 X



# **Product Specification Sheet**

Partcode: ILMR16NE030 / Page: 3

#### **Environmental**



Energy Rating: A+

Lowest Operating Temperature: -20 degrees

Maximum Operating Temperature: 40 degrees

IP (Ingress Protection) Rating: IP20

Hg 0% (Mercury Free): Yes

### **Packaging**

EAN Barcode (unit of 1): 5055788231264

Packaged Weight (Unit of 1): 63g

Length (unit of 1): 60mm Width (unit of 1): 55mm Depth (unit of 1): 55mm

Outer packaging info available on website

Product data last updated on: Tuesday, September 8, 2020 - 22:14