

Pro Bollard Lighting

Exterior Lights UK Ltd.

IN-GROUND PROFESSIONAL ROOT MOUNT SYSTEM

For use with all Ledifice / Lighthouse / Fortress Lumena Pro Bollards

78cm (for 0.6m Bollards) / 99cm (for 0.8m Bollards) / 119cm (for 1.0m Bollards)

INPUT: 220-240v - 50Hz

MAX WATTAGE: 70w

PROTECTION: Class I




BULB HOLDER: ES/E27

MATERIALS: ALUMINIUM & STEEL

Always switch off mains supply prior to installation


Included:

- 1 x Root Mount Tube
- 1 x Bulb Holder / Connection Box
- 1 x Anchor Bar & 2 x Locking Nuts
- 1 x M20 Cable Gland & Locking Nut (Optional)
- 2 x Security Screws (Pin Hex) & Allen Key




Installation:

- Insert anchor bar through the tubular body via the pre drilled holes approx. 100mm from the base and secure in place with the 2 x locking nuts (a).
- Optional:** If cable entry is preferred through the side of the bollard instead of through the centre of the base, drill a 20mm hole where desired and secure the cable gland in place securing with the locking nut on the inside of the bollard.
- Select a suitable mounting position and dig an installation hole sufficient to accommodate at least 40cm of the length of the bollard and the width of the anchor bar.
- Ensure enough cable is in place to reach the connection box at the top of the bollard, plus 30cm extra for ease of wiring.
- Position bollard in place pulling the cable up through the centre (or through cable gland as referenced above) and concrete the surrounding area to secure in place. Leave to set.



See Main Instructions for Additional Safety Information, Wiring and Re-assembly Instructions

www.exteriorlightsuk.co.uk



Pro Bollard Lighting

Exterior Lights UK Ltd.

IN-GROUND PROFESSIONAL ROOT MOUNT SYSTEM

For use with all Ledifice / Lighthouse / Fortress Lumena Pro Bollards

78cm (for 0.6m Bollards) / 99cm (for 0.8m Bollards) / 119cm (for 1.0m Bollards)

INPUT: 220-240v - 50Hz

MAX WATTAGE: 70w

PROTECTION: Class I




BULB HOLDER: ES/E27

MATERIALS: ALUMINIUM & STEEL

Always switch off mains supply prior to installation


Included:

- 1 x Root Mount Tube
- 1 x Bulb Holder / Connection Box
- 1 x Anchor Bar & 2 x Locking Nuts
- 1 x M20 Cable Gland & Locking Nut (Optional)
- 2 x Security Screws (Pin Hex) & Allen Key



Installation:

- Insert anchor bar through the tubular body via the pre drilled holes approx. 100mm from the base and secure in place with the 2 x locking nuts (a).
- Optional:** If cable entry is preferred through the side of the bollard instead of through the centre of the base, drill a 20mm hole where desired and secure the cable gland in place securing with the locking nut on the inside of the bollard.
- Select a suitable mounting position and dig an installation hole sufficient to accommodate at least 40cm of the length of the bollard and the width of the anchor bar.
- Ensure enough cable is in place to reach the connection box at the top of the bollard, plus 30cm extra for ease of wiring.
- Position bollard in place pulling the cable up through the centre (or through cable gland as referenced above) and concrete the surrounding area to secure in place. Leave to set.



See Main Instructions for Additional Safety Information, Wiring and Re-assembly Instructions

www.exteriorlightsuk.co.uk